



Collier avec profil en caoutchouc prémonté en 1 pièce

- Collier zingué
- Profil EPDM selon ISO 1629
- Temp.: -50° à +110°C

mm	Ø	Connec- tion	Pkg	Art n°
12-16	1/4"	M8	100	W220251
17-19	3/8"	M8	100	W220252
20-23	1/2"	M8	100	W220253
25-30	3/4"	M8	100	W220254
31-38	1"	M8	100	W220255
40-46	1 1/4"	M8	100	W220256
48-23	1 1/2"	M8	50	W220257
60-64	2"	M8	50	W220259
17-19	3/8"	M8/10	150	W220202
20-23	1/2"	M8/10	100	W220203
25-30	3/4"	M8/10	100	W220204
31-38	1"	M8/10	75	W220205
40-46	5/4"	M8/10	50	W220206
48-23	6/4"	M8/10	50	W220207
50-56	54mm	M8/10	50	W220208
60-64	2"	M8/10	50	W220209
63-67	63 mm	M8/10	50	W220210
74-80	2 1/2"	M8/10	50	W220212
87-92	3"	M8/10	50	W220214
102-116	4"	M8/10	25	W220216
122-132	125mm	M8/10	25	W220217
159-168	6"	M8/10	25	W220221